

.4 hp Drill

Right Angle, 9/32"-40 Thread

PD12-19R
Effective March, 2025
Supersedes PD12 -19

Safety, Operation and Maintenance – Save This Document and Educate All Personnel

Model	Drill Type	RPM
49431	Standard	3,200

DRILL



Model 49431

LIMITED
LIFETIME
WARRANTY

Find The Most Current Offering of Support Documents and Accessories at www.Dynabrade.com

⚠ WARNING

Read and understand this tool manual before operating your air tool. Follow all safety rules for the protection of operating personnel as well as adjacent areas. Always operate, inspect and maintain this tool in accordance with the American National Standards Institute (ANSI). Safety Requirements for abrading materials with coated abrasive systems - ANSI B7.7, Compressed Air and Gas Institute (CAGI) Safety Code for Portable Air Tools - B186.1, Code of Federal Regulation - CFR 29 Part 1910, International Organization for Standardization (ISO) Hand Held Non-Electric Power Tools - Safety Requirements ISO 11148-8 and applicable State and Local Regulations.



Read and understand tool manual before work starts to reduce risk of injury to operator, visitors, and tool.



Eye protection must be worn at all times, eye protection to conform to ANSI Z87.1.



Ear protection to be worn when exposure to sound, exceeds the limits of applicable Federal, State or local statutes, ordinances and/or regulations.



Practice safety requirements. Work alert, have proper attire, and do not operate tools under the influence of alcohol or drugs.



Respiratory protection to be used when exposed to contaminants that exceed the applicable threshold limit values required by law.



Air line hazard, pressurized supply lines and flexible hoses can cause serious injury. Do not use damaged, frayed or deteriorated air hoses and fittings.

Some dust created by sanding, grinding, drilling, and other construction activities contain chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- Lead from lead-based paints
- Crystalline silica from bricks and cement and other masonry products
- Arsenic and chromium from chemically treated lumber

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

SAFETY and OPERATING INSTRUCTIONS



Carefully Read and Understand the General and Sander/Polisher sections found in Tool Safety and Operating Guidelines (PN00001676) Before Handling or Using Tool.

Carefully Read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool. Products offered by Dynabrade are not to be modified, converted or otherwise altered from the original design.

Tool Intent: Drills are intended to be used by professional operators for drilling holes in a variety of materials using 9/32"-40 threaded drill bits or accessories. Follow all safety guidelines for material being processed.

DO NOT USE Tool for Anything Other Than Its Intended Applications.

Training: Proper care, maintenance, and storage of your air tool will maximize tools performance and reduce chance for accident.

Employer's Responsibility: Provide operators with safety instructions and training for safe use of tools and accessories.

Report to Your Supervisor any Condition of the Tool, Accessories or Operation you Consider Unsafe.

MAINTENANCE INSTRUCTIONS

Important: To keep tool safe, a Preventative Maintenance Program is recommended. The program should include inspection of the tool and all related accessories and consumables, including air lines, pressure regulators, filters, oilers, etc. (refer to CAGI B186.1 for additional maintenance information). If accessory or tool breakage occurs, investigate failure to determine the cause and correct before issuing tool for work. Use the following schedule as a starting point in developing a Preventative Maintenance Program. If tool does not operate properly (RPM, vibration, start/stop) after these scheduled checks or at any time, the tool must be repaired and corrected before returning tool to use.

INSTALLATION


- To ensure long life and dependable service, use a Closed Loop Air System and Filter-Regulator-Lubricator (FRL) as diagramed below.
- Each tool should have its own dedicated hose connected to an air supply FRL. Quick disconnects should be installed at the FRL in an effort to reduce contamination into the tool. Securely affix all fittings and hose assemblies.
- It is strongly recommended that all Dynabrade rotary vane air tools be used with a Filter-Regulator-Lubricator to minimize the possibility of misuse due to unclean air, wet air or insufficient lubrication. Dynabrade recommends the following: **10690** Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components.
- Dynabrade recommends 1 drop of air lube per minute for each 20 SCFM (example: if the tool specification states 40 SCFM, set the drip rate on the filter-lubricator to 2 drops per minute). **95842** Dynabrade Air Lube is recommended.

MAINTENANCE SCHEDULE

Maintenance schedules depend on the type and style of tool. Refer to page 3 to reference symbols associated with specific maintenance items/areas. Match maintenance schedules accordingly. See page 4 for any additional maintenance information.

Note: Turbine style air motors do not require oil.

Daily (every 8 hours):

- Inspect tool and accessories for damage or broken parts. Replace items as necessary to ensure proper operation and safety.
-  Lubricate motor as recommended. Use **95842** Dynabrade Air Lube (10W/NR). Apply 1 drop/minute of air lube per 20 SCFM.
- Check air line pressure with a gage. (MAX. 90 PSIG or 6.2 Bar operating pressure at the air inlet of the tool.)
- Check tool for proper operation: If operating improperly or demonstrates unusual vibration, the tool must be serviced and problem corrected before further use.

Every 20 Hours/Once a Week (which ever comes first):


- Measure RPM (speed) by setting air pressure to 90 PSIG (6.2 Bar) at tool inlet, without accessory mounted, while the tool is running. Using tachometer, check spindle speed of the tool. Unless otherwise stated the no-load speed may not exceed the rated speed. If tool speed exceeds maximum rated RPM, service as required and correct before use.
- If tool is running too fast: look for worn, damaged or missing governor, air

control rings and silencer(s). Service as required.

- If tool is running too slow: look for malfunctioning governor, clogged inlet screen, silencer(s) or air stream. Service as required.


Note: Special care must be taken when servicing governors. Refer to specific tool manual for governor instructions and/or speed control devices. Governor assemblies made from molded plastic components are non-serviceable and must be replaced.

Every 500 Hours:

-  Both the right angle gears and the planetary gears are packed with **96664** Dynabrade Ultra Gear Grease and neither are externally serviceable. When servicing tools or at a 500-hour interval, flush grease from tool and inspect wear of parts. Replace parts as needed and repack grease areas by liberally applying grease to the areas depicted on page 3.

REPAIR

- Use only genuine Dynabrade replacement parts to ensure quality. To order replacement parts, specify Model#, Serial# and RPM of your air tool.
- Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters, ketones, chlorinated hydrocarbons or nitro carbons.
- A Motor Tune-Up Kit is available which includes high wear and medium wear motor parts.
- Air tool markings must be kept legible at all times, if not, reorder housing and replace. User is responsible for maintaining specification information.

-  After maintenance is performed on tool, add a few drops of **95842** Dynabrade Air Lube to the tool inlet and start the tool a few times to lubricate air motor. Verify RPM (per 20 hr maintenance schedule), vibration and operation.

HANDLING & STORAGE

- Use of tool rests, hangers and/or balancers is recommended.
- Protect tool inlet from debris (see Notice below).
- **Do Not** carry tool by air hose or near the tool throttle lever.
- Store accessories in protective racks or compartments to prevent damage.
- Follow the handling instructions outlined in the operating instructions when carrying the tool and when changing accessories.
- Protect accessories from exposure to water, solvents, high humidity, freezing temperature and extreme temperature changes.

END OF USE/DISPOSAL

When tool has reached its end of useful service, disassemble tool into its primary components (i.e. steel, aluminum and plastic) and recycle or discard per local, state and/or federal regulations as to not harm the environment.


NOTICE

All Dynabrade air motors use the highest quality parts available and are manufactured to exacting tolerances. Air motor failures are often traced to lack of lubrication or unclean air supply. Compressed air can force dirt and other contaminants into motor bearings causing early failure. Contaminants can score cylinder wall and vanes resulting in reduced efficiency and power. Our warranty obligation is contingent upon proper use of our tools. Air motors which have been subjected to misuse, contaminated air or lack of lubrication will void warranty.

CLOSED LOOP AIR SYSTEM

Sloped in Direction of Air Flow


- Dynabrade Air Power Tools are designed to operate at 90 PSIG (6.2 Bar) maximum air pressure at the tool inlet, when the tool is running. Use recommended regulator to control air pressure.
- Ideally the air supply should be free from moisture. To facilitate removing moisture from air supply, the installation of a refrigerated air dryer after the compressor and the use of drain valves at each tool station is recommended.



Lubricator Setting

1 Drop/Minute per 20 SCFM

ITEM	P/N	DESCRIPTION	QT
1	58564	ANGLE HEAD ASSEMBLY	1
1.1	54550	BEARING CAP	1
1.2	54537	BEARING	1
1.3	58568	WORK SPINDLE	1
1.4	54542	BEARING	2
1.5	54536	SHIM PACK (4/PKG)	1
1.6	54577	PLUG	1
1.7	54547	ANGLE HOUSING	1
1.8	54546	BEVEL GEAR	1
1.9	54576	SPINDLE	1
1.10	54529	SHIM PACK (3/PKG)	1
1.11	95398	BEARING	1
1.12	54540	RETAINING NUT	1
2	54527	LOCK RING	1
3	53451	ADAPTER	1
4	53450	DRIVE SPLINE	1
5	54520	BEARING	2
6	54468	RING GEAR	1
7	50786	PLANETARY CARRIER	1
8	54519	GEAR ASSEMBLY	2
9	54472	SHAFT	2
10	58565	GEAR CASE	1
11	01547	INSULATOR COLLAR	1
12	45298	SHORT BLOCK ASSY	1
12.1	02649	BEARING	1
12.2	01478	FRONT BEARING PLATE	1
12.3	50767	PIN	2
12.4	01479	SPACER	1
12.5	01480	VANE (4/PKG)	1
12.6	45292	ROTOR	1
12.7	01476	CYLINDER	1
12.8	02676	REAR BEARING PLATE	1
12.9	02696	BEARING	1
13	45269	GOVERNOR (BLUE)	1
14	45320	GOVERNOR CHAMBER	1
15	45305	HOUSING	1
16	96077	O-RING	1
17	09726	SLEEVE	1
18	45315	BUSHING	1
19	58597	PIN	1
20	45263	THROTTLE LEVER	1
21	97060	PIN	1
22	58596	SEAL	1
23	01472	TIP VALVE	1
24	52943	SPRING	1
25	01564	AIR CONTROL RING	1
26	94535	MUFFLER ASSY - 0.4 HP	1
26.1	95711	SNAP RING - 5/8 IN	1
26.2	01486	FELT SILENCER	4
26.3	96065	O-RING	1
26.4	01446	AIR DEFLECTOR	1
26.5	95620	RETAINING RING - 17 MM	1
26.6	01578	ADAPTER ASSY - INLET	1
-	51694	SHAFT LOCK ASSEMBLY-PENCIL GRINDER	1
-	95987	WRENCH - 5/16"	1



KEY	
O	Oil: O ₁ = Air Lube
A	Adhesive: A ₂ = Loctite #271 A ₈ = Loctite #567 A ₁₀ = Loctite #243 A ₁₇ = Loctite #454
T	Torque: N•m x 8.85 = In. - lbs.
G	Grease: G ₄ = Ultra Gear Grease

Always follow adhesive manufacturers cleaning and priming recommendations.

LIMITED LIFETIME WARRANTY

To validate Dynabrade Limited Lifetime Warranty, you must register each tool at: www.dynabrade.com. Registration of each tool at website is required. Dynabrade will not honor Limited Lifetime Warranty on unregistered tools. Please view the entire Limited Lifetime Warranty Policy at: www.dynabrade.com.

LIMITED
LIFETIME
WARRANTY

MACHINE SPECIFICATIONS

Model	Speed	Power	Sound	Air Consumption	Air Pressure	Weight	Length	Height
49431	3,200 RPM	.4 hp (298 W)	79 db(A)	26 SCFM (736 LPM)	90 PSIG (6.2 Bars)	1.8 lb. (.80 kg)	10.5" (266 mm)	1.0" (26 mm)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. 1/4" (6 mm)

Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744

OPTIONAL ACCESSORIES



Motor Tune-Up Kit

- Includes assorted parts to help maintain and repair motor.

Part No. 96541



Dynabrade Air Lube

- Formulated for pneumatic equipment.
- Absorbs up to 10% of its weight in water.
- Prevents rust and formation of sludge.
- Keeps pneumatic tools operating longer with greater power and less down time.

Part No. 95842: 1pt. (473 ml)

Part No. 95843: 1 gal. (3.8 L)



Dynaswivel®

- Swivels 360° at two locations which allows an air hose to drop straight to the floor, no matter how the tool is held.


Part No. 94300 – 1/4" NPT.



Ultra Gear Grease

- Multi-purpose grease for all types of bearings, cams, gears.
- High film strength; excellent resistance to water, steam, etc.
- Workable range 0° F to 300° F

Part No. 96664: 10 oz. (283.5 g) Tube.



Hex Key Wrench

- 12 mm hex
- Use in housing core or air inlet.

Part No. 96399



Crowfoot Wrench

- 3/8" Drive
- 34 mm
- Use on throttle body, housing core and lock nuts.

Part No. 96460



Overhose Assembly

- Redirects exhaust away from operator.

Part No. 94995



Lock Ring Tools

Part No. 96165

- For removal/tightening of 58564 Bearing Cap.

Part No. 97782

- For removal/tightening of 53451 Adapter.

REFERENCE CONTACT INFORMATION

American National Standards Institute (ANSI)

www.ansi.org

Compressed Air & Gas Institute (CAGI)

www.cagi.org

European Committee for Standardization (PNEUROP)

www.pneurop.org

International Organization of Standards (ISO)

www.iso.org

U.S. Government Publishing Office (GPO)

www.gpo.gov

DYNABRADE, INC.

www.dynabrade.com

8989 Sheridan Drive • Clarence, NY 14031-1419 • Phone: (716) 631-0100 • Fax: 716-631-2073 • International Fax: 716-631-2524

© DYNABRADE, INC., 2025

PRINTED IN USA

PD12-19R_02/25

